



## AutoCal V3 Hardware Specification

Cindy Myers - 2020-08-28 - Comments (0) - AutoCal V3 Hardware Configuration

### AutoCal V3 Specification

- SAE-J1979 CAN protocol.
- SAE-J1850 VPW protocol.
- SAE-J1939 CAN protocol.
- Large, easy to read color screen.
- Built in 512MB micro SD Card stores hundreds of tune files and/or hundreds of hours of logged data.
- Upgradeable firmware.
- Vehicle Input Voltage - Min 9V, Max 28V.
- Battery backed real-time clock for accurate timestamps.
- Appears as a Windows USB drive.
- Built-in power supply prevents data corruption if external power supply is interrupted.
- Supports 600 VIN Licenses. (Some AutoCal devices may be configured by the supplier with a smaller maximum VIN license limit.)

### Systems Requirements

- PC or laptop capable of running Win7 or higher
- USB port
- Color screen with 1280x960 or greater resolution
- 1GB of available disk space

### Integrates with:

- FlashScan V3, FlashScan V2 and FlashScan HD. AutoCal cannot be used to create, edit or save tune files; a FlashScan device is required by the tuner to perform these functions.
- [Serial cable \(RJ12 to RS232 9-pin female\).](#)
- [WO2 Serial Adapter \(Null Modem\) Male.](#)
- [FlashScan Expansion cable.](#)
- [Black J1939 Male to OBDII Female Adapter.](#)
- [Green J1939 Male to OBDII Female Adapter.](#)