



V3 USB FAQ

Cindy Myers - 2020-08-12 - Comments (0) - AutoCal V3 Hardware Configuration

FlashScan/AutoCal V3 devices appear as a Windows USB drive in Windows Explorer. There are no external drivers to install. There are a number of potential reasons why FlashScan/AutoCal V3 will not connect via USB.

1. Ensure you are using the heavy gauge EFILive USB cable that shipping with your device.
2. Ensure you have downloaded and installed the latest version of EFILive's V8 software, available [here](#).
3. Rapid connection/disconnection of **FlashScan/AutoCal V3's** USB cable may cause **FlashScan/AutoCal V3** to fail to power up via USB connection. If the device does not power up with 10 seconds of a USB connection, you can reset **FlashScan/AutoCal V3** by powering up via the OBDII connection.
4. With **FlashScan/AutoCal V3** connected to your PC, open V8 Scan and Tune software and select the **[Check Firmware]** option. Install any pending updates.
5. On **FlashScan/AutoCal V3** navigate to **Options -> F1: Setup -> F3: Update Boot Block** and install any pending boot block updates.
6. For some computers running Windows 7 it may be necessary to install WINUSB drivers. Please refer to the [WINUSB Drivers for FlashScan/AutoCal V3 on Windows 7](#) knowledgebase article.

Related Content

- [V3 Firmware and Boot Block](#)
- [WINUSB Drivers for FlashScan/AutoCal V3 on Windows 7](#)